STOPOUT

Blind Flange Lockout

Effectively lockout and prevent unintentional pipe blind removal during maintenance. The adjustable Blind Flange Lockout fully conceals flange bolts eliminating the opportunity to remove ALL bolts and prevent removal of blind.

- · Constructed of durable, high-impact plastic to withstands harsh environments
- Ideal for use in temperature of -4°F to 140°F
- · Maximum shackle diameter 9/32"
- · Adjustable device provides a tight fit

KDD501 - Class 150 - Nominal Pipe Size = .5, .75, 1.0, 1.25, and 1.50

Class 300 - Nominal Pipe Size = .5, .75, 1.0, and 1.25

 $KDD502 - Class\ 150 - Nominal\ Pipe\ Size = 2.0,\ 2.50,\ 3,\ 3.5,\ 4.0,\ 5.0,\ 6.0,\ and\ 8.0$

Class 300 - Nominal Pipe Size = 2.0, 2.50, 3, 3.5, 4.0, 5.0, and 6.0

KDD503 - Class 150 - Nominal Pipe Size = 10.0 and 12.0

Class 300 - Nominal Pipe Size = 8.0



Class 150 Fits Nut Diameter	Class 300 Nut Diameter	Class 150 Pipe Diameter	Class 300 Pipe Diameter	Pipe Flange Width Range	No.	Unit
.62"88" (15.74mm - 22.35mm)	.62"88" (15.74mm - 22.35mm)	.5, .75, 1.0, 1.25, and 1.50 (12.7, 19.05, 25.4, 31.75 and 38.1mm)	.5, .75, 1.0, & 1.25 (12.7, 19.05, 25.4, 31.75 and 38.1mm)	1-1/2" – 5-5/8" (38.1mm – 143.3mm)	KDD501	Each
.75"88" (19.05mm - 22.35mm)	.75" – 1.00" (19.05mm –25.4mm)	2.0, 2.50, 3, 3.5, 4.0, 5.0, 6.0, and 8.0 (50.8, 63.5, 76.2, 88.9, 101.6, 127, 152.4, and 203.2mm)	2.0, 2.50, 3, 3.5, 4.0, 5.0, and 6.0 (50.8, 63.5, 76.2, 88.9, 101.6, 127 and 152.4mm)	3-3/4" - 10-3/4" (95.3mm - 274.6mm)	KDD502	Each
1" (25.4mm)	1" (25.4mm)	10" and 12" (254mm and 304.8mm)	8.0 (203.2mm)	7-3/4" - 17-7/8" (196.9mm - 447.8mm)	KDD503	Each



Isolation Blind Tags

Alert workers to the location and specific hazards of blinds installed during maintenance or lock out. Isolation Blind Tags clearly identify and warn employees that maintenance or other procedures are in progress. Blind Tags aid your efforts to comply with OSHA's Standard 29 CFR 1910.146(b).

- · Attention grabbing flag design and bright colors
- Ideal for indoor and outdoor use
- · RV-Plastic material is abrasion-resistant
- Measures 2" x 21" and includes a 3/8" metal grommet
- · Available in packs of 5 or 25 alike tags

ISOLATION BLIND

MDT507

• INSTALL BLIND

MDT508

INSTALL BLIND HERE

MDT503

• BLIND INSTALLED

MDT505

BLIND INSTALLED

CONFINED SPACE BLIND

MDT504

• BLIND INSTALLED

MDT502

• DO NOT OPERATE

MDT510

• BATTERY LIMIT BLIND

MDT511

To order, add pkg. code after part number.

Price per Package of	5	Price per Package of 25		
Code	Unit	Code	Unit	
PTM	Pkg. of 5	PTP	Pkg. of 25	

▲ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

MKTBLNDTGLITUS | © 2021 Accuform. All rights reserved.

